

## IMPER ESMALTE PULIDO

### DESCRIPTION

WATER REPELLENT FOR POLISHED GLAZE CERAMIC FLOOR OR ALIKE

### CHARACTERISTICS

Water repellent system modified silicon and synthetic resin base, used to waterproof glaze ceramic floor, semi matt ceramic, extruded ceramics....

### SPECIFICATIONS

Aspect	Colourless liquid
Colour	Colourless
Density	0,80 - 0,85 g/ml

### APPLICATIONS

The product application is aimed at making the polished or semi-polished ceramic floor water repellent. IMPER POLISHED GLAZE use enables an easier cleaning process for fat stains, colouring and other kind of dirtiness. IMPER POLISHED GLAZE fulfils the cavities originated by the polish process and avoids dirtiness to settle into them, easing the surface cleaning process.

### INSTRUCTIONS

The surface must be completely clean and dry prior to the use of the product. It must be applied through pulverization with a low-flow tip. The product reaches it best effectiveness 24 hours after its application. As a general standard, the quantity of the product needed can be calculated having as a reference 6-10 gr/m<sup>2</sup>. An extra consumption, origins a superficial tuning\_which can be removed with cleaning alcohol (methyl alcohol) or acetone.

For its hand application, use a piece of cloth or a pad to rub slightly on the surface with a small amount of IMPER POLISHED GLAZE. Leave it acting for 5 minutes and afterwards with a cellulose paper clean the surface avoiding leaving traces of the product. Dirtiness and stain tests are to be conducted 24 hours after the application of the product.

### RECOMMENDATIONS

It is highly recommended to perform a previous test before a massive application of the product. It is recommended to use the product in ventilated premises and to avoid smoking.

### STORAGE


In closed containers, the product can be stored 12 months. Do not expose the product to 30°C or higher temperatures and avoid direct sunlight contact.

### PACKAGING

25 and 200 litres recipients.  
1000 litres containers.

### RISK & SAFETY PHRASES AND HAZARD SYMBOLS

R10	Flammable.
R20	Harmful by inhalation.
S24/25	Avoid contact with skin and eyes.



The information and recommendations indicated on this technical data sheet reflect our current knowledge, laboratory experiments and normal experience. For this reason, our guarantee is limited to the quality of the product supplied. This company shall not assume any liability arising from misuse of our products.